




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E05F 1/00		A1	(11) International Publication Number: WO 00/11296
			(43) International Publication Date: 2 March 2000 (02.03.00)
(21) International Application Number: PCT/NZ99/00139		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KB, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 16 August 1999 (16.08.99)			
(30) Priority Data: 331456 19 August 1998 (19.08.98) NZ			
(71) Applicant (for all designated States except US): FISHER & PAYKEL LIMITED [NZ/NZ]; 78 Springs Road, East Tamaki, Auckland (NZ).			
(72) Inventors; and			
(75) Inventors/Applicants (for US only): SPONG, Keith, Brookes [AU/NZ]; 2 Te Akau Crescent, Bucklands Beach, Auckland (NZ). FULLER, Graeme, Colin [NZ/NZ]; Unit 4, 121 Bayview Road, Dunedin (NZ). DUNCAN, Gerald, David [NZ/NZ]; 12 Cedar Road, Epsom, Auckland (NZ).		Published With international search report.	
(74) Agents: CALHOUN, Douglas, C. et al.; A J Park & Son, Huddart Parker Building, 6th floor, Post Office Square, P.O. Box 949, Wellington 6015 (NZ).			

(54) Title: DOOR OPENING AND CLOSING SYSTEM

(57) Abstract

A door state changing apparatus assists a user to move a door between a closed state where the door (8, 9) is positioned adjacent a door frame and an open state. The door state changing apparatus includes a permanent magnet (13, 14) provided on the door and having a permanent magnetic field. An electromagnet (11, 12) is located on the door frame adjacent the permanent magnet with the door in a closed state and is energisable to provide a magnetic field which reinforces the permanent magnetic field of the permanent magnet or to provide a magnetic field in opposition to the permanent magnetic field of the permanent magnet. A door position detector detects the open or closed state of the door and a user interface detects the presence of a user attempting to alter that state. A controller (6) receives input from the door position detector and the user interface and energises the electromagnet (11, 12) to provide a reinforcing magnetic field if a user is attempting to move the door (8, 9) from an open state to a closed state and provides an opposing magnetic field to the permanent magnetic field of the permanent magnet if the door is closed and the user interface indicates that a user is attempting to open the door. The invention is particularly adapted for use in a domestic refrigerator.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

"DOOR OPENING AND CLOSING SYSTEM"

FIELD OF THE INVENTION

5 This invention relates to door opening and/or closing and/or latching devices and especially though not solely to devices which may be used in conjunction with home appliance doors, such as refrigerator doors to assist in opening and closing these doors.

BACKGROUND TO THE INVENTION

10 A conventional door must be opened by physically pulling on the door and closed by physically pushing on the door. In order to maintain the door in a closed position a latch is often incorporated so that opening and closing then also involves physically connecting and disconnecting the latch mechanism.

15 In refrigerator cabinets, the doors there has long been a problem of holding the door closed in order that cooled air does not escape thereby warming and spoiling the contents. Refrigerator doors have been fitted with a gasket which is often formed from a plastic material which seals between the door and the door frame. The gasket often has a permanent magnetic strip incorporated therein which assists in holding and sealing the door to the door frame. The gasket has been
20 designed to incorporate the aforementioned magnetic strip and has not, therefore, been designed with optimal thermal sealing properties in mind and this aspect of its design could be improved. Also, the fact that the magnet is positioned in the gap between the door and frame means that it provides a path for heat conduction into the refrigerator cabinet through this gap. In addition, the magnet necessitates the use
25 of metal door frame surrounds in order that the magnet may be attracted to the door frame thus providing a further path for heat conduction from the interior of the refrigerator cabinet. Furthermore, the assembly of the magnetic strip in the door gasket is a source of assembly cost due to the time and labour required which could be eliminated. However, even when this magnetic gasket is used it is often still
30 necessary to arrange the refrigerator cabinet so that the front is raised slightly above the level of the back ensuring that the door is always biased towards a closed

position. However, it is still possible for a user to have seemingly closed the door when in reality there is still a gap between the door and frame which the existing permanent magnet can not possibly close.

5 In an effort to overcome this problem some refrigerator manufacturers have developed devices which prevent refrigerator doors from resting in an almost closed position. An example of such a device is disclosed in United States patent number US5,138,743 (assigned to White Consolidated Industries Inc.) wherein the hinge pin is attached to the cabinet through a bracket and is provided with lobe shaped camming surfaces around the pin and complementary lobe shaped camming surfaces
10 are also provided around an aperture in the door. The two camming surfaces arranged so that the door will tend to rotate to a position where the lobes fit together which is arranged to be where the door would ordinarily close or even beyond the normal closing position so that a closing force is always applied to the door when it meets the door frame.

15 Another problem in present refrigerator cabinet door designs (especially large doors) is that when the door has been closed and a good seal is established between the door and frame, it is necessary to supply a relatively large force to the door in order to open it. This is disadvantageous in modern home appliances which are expected to be easy to operate and, in the case of refrigerator doors, repeatedly and
20 easily opened with a consistent force. A door which could be reliably closed without the need for the user to occasionally manually check that this is the case would also be an improvement.

Examples of improved door latching systems and door opening/closing systems which utilise a combination of permanent and electromagnets are disclosed
25 in United States Patent numbers US3,635,511 (Waller), US3,647,165 (Whitla), US3,658,370 (Wang), US3,764,172 (Standke), US3,860,277 (Wang), US4,428,607 (Levine), US4,506,407 (Downey) and US5,293,020 (Han et al). However, none of the aforementioned systems are intended for use in refrigerator cabinets and do not incorporate the necessary user sensing hardware and associated logic. Furthermore,
30 many of the systems disclosed require a mechanical latching mechanism in association with the magnetic components.

It is, therefore, an object of the present invention to provide a door opening, closing and/or holding system which will at least go somewhat towards overcoming the above disadvantages or which will at least provide the public with a useful choice.

5

SUMMARY OF THE INVENTION

In one aspect the invention consists in door state changing apparatus for assisting a user to move a door between a closed state where the door is positioned adjacent a door frame and an open state comprising:

10 permanent magnet means on or attached to said door to provide a permanent magnetic field,

electromagnet means on or attached to said door frame adjacent said permanent magnet means when said door is in said closed state, which electromagnet means is energisable to provide a magnetic field in a first direction to
15 reinforce said permanent magnetic field and energisable to provide a magnetic field in a second direction to oppose said permanent magnetic field

door position detection means to detect the state of said door,

user interface means to detect the presence of a user attempting to alter the state of said door, and

20 control means which receives input from said door position detection means and said user interface means and provides a control signal to energise said electromagnet means to provide a magnetic field in said first direction if said user interface means indicates a user is attempting to alter the state of said door and said door position detection means indicates that said door is in said open state and
25 provides a control signal to energise said electromagnet means to provide a magnetic field in said second direction if said user interface means indicates a user is attempting to alter the state of said and said door position detection means indicates that said door is in said closed state.

In a further aspect the invention consists in a home appliance including a
30 cabinet and a door hingeably connected to said cabinet and closeable against a door frame said appliance including door state changing apparatus for assisting a user to

move said door between a closed state and an open state where said door is positioned adjacent said door frame and an open state, said door state changing apparatus comprising:

5 permanent magnet means on or attached to said door to provide a permanent magnetic field,

electromagnet means on or attached to said door frame adjacent said permanent magnet means when said door is in said closed state, which electromagnet means is energisable to provide a magnetic field in a first direction to reinforce said permanent magnetic field and energisable to provide a magnetic field
10 in a second direction to oppose said permanent magnetic field

door position detection means are also provided to detect the state of said door,

15 user interface means to detect the presence of a user attempting to alter the state of said door, and

control means which receives input from said door position detection means and said user interface means and provides a control signal to energise said electromagnet means to provide a magnetic field in said first direction if said user interface means indicates a user is attempting to alter the state of said door and said
20 door position detection means indicates that said door is in said open state and provides a control signal to energise said electromagnet means to provide a magnetic field in said second direction if said user interface means indicates a user is attempting to alter the state of said and said door position detection means indicates that said door is in said closed state.

25 In a still further aspect the invention consists in a refrigerator including door state changing apparatus as set forth above.

To those skilled in the art to which the invention relates, many changes in construction and widely differing embodiments and applications of the invention will suggest themselves without departing from the scope of the invention as defined
30 in the appended claims. The disclosures and the descriptions herein are purely illustrative and are not intended to be in any sense limiting.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a partially cut away perspective view of a refrigerator incorporating the preferred form of the present invention cabinet with both compartment doors open, and

Figure 2 is a flow diagram showing the operation of the preferred form of the present invention on either one of the refrigerator or the freezer compartments of the refrigerator shown in Figure 1.

DETAILED DESCRIPTION

With reference to the drawings and in particular Figure 1, a refrigerator cabinet 1 incorporating the door opening and/or closing system according to one preferred embodiment of the present invention is shown. Although the preferred embodiment of the invention will be described with reference to a refrigerator cabinet, however, it should be apparent to those of ordinary skill in the art that the invention is equally applicable to most if not all doors which require some form of seal such as chest freezers, microwave ovens, and could even be used in doors which do not require a seal such as household doors.

The refrigerator cabinet 1 shown in Figure 1 is provided with a refrigeration compartment 2 (sometimes referred to as the "product compartment") and a freezer compartment 3, adapted to be cooled by a refrigeration system (not shown) to respective temperatures. The refrigeration compartment 2 and the freezer compartment 3 each comprise side walls, top wall, bottom wall and rear wall with a front opening provided to allow items of food to be placed within the compartments. Normally the refrigerator cabinet would be formed from sheet steel, however it should be appreciated that the present invention will allow the cabinet to be formed from a plastics material. A refrigeration compartment door 4 is attached, for example by hinges (not shown) to one edge of the cabinet 1 in order to close the front opening of the refrigeration compartment. Similarly, a freezer door 5 is attached to an edge of the cabinet 1 to close the front opening in the freezer compartment. Gaskets 9 and 10 are provided around the periphery of the internal

surface of the refrigerator and freezer compartment doors 4 and 5 respectively. Gaskets 9 and 10 are preferably formed from a flexible and compliant yet heat insulating material such as a standard plastics refrigerator door seal (although a "standard" refrigerator door sealing gasket is fitted with a magnetic strip to bias the door closed against the normally metallic compartment, the magnetic strip is not required in the gasket according to the preferred form of the present invention and thus, as previously mentioned, the cabinet could be formed from a plastics material).

A control means or electronic controller 6 (which may comprise a microprocessor with associated circuitry and memory storage devices) is positioned within cabinet 1. Controller 6 preferably stores and executes a software program which controls the operation of the refrigerator. In addition to controlling the temperature of the refrigeration and freezer compartments of the refrigerator (by controlling the refrigeration system and the states of any valves or fans in the path of cooled air from the refrigeration system to the compartments 2 and 3) controller 6 also receives input from door sensors, for example touch sensitive pads 7 and 8 positioned on the refrigeration and freezer compartment doors respectively.

Means for locking and unlocking compartment doors 4 and 5 are provided in each compartment. Preferably the means for locking and unlocking comprise electromagnets 11 and 12 provided in one of the walls of refrigerator compartment 2 and freezer compartment 3 respectively. Electromagnet 11 is connected for energisation to controller 6 and is preferably positioned in such a way as to produce separated poles (11A, 11B) in a plane parallel with a front facing wall of the compartment. The electromagnet is preferably able to be energised in either direction so that pole 11A could be a North or a South pole on demand. Electromagnet 11 is preferably positioned within one of the compartment walls but adjacent a surface which is in contact with or nearly contacts a part of the refrigerator compartment door when closed. The construction and arrangement of electromagnet 12 is preferably the same as that described above with reference to electromagnet 11. It should be noted that the positioning of the electromagnets 11 and 12 is not crucial and could be altered. For example, the electromagnets could be positioned in the front facing vertical wall of the cabinet furthest from the hinges.

Complimentary to each of electromagnets 11 and 12 are door mounted keeper means 13 and 14 positioned respectively in parts of the refrigerator and freezer doors which are adjacent the compartment electromagnets when the doors are shut or nearly shut. It can be seen in the example shown in Figure 1 that the keeper means
5 are provided in the lower edge of each door. Preferably the keeper means are formed from a ferromagnetic substance so that they are attracted towards their respective electromagnets when energised. More preferably, the keeper means are actually permanent magnets with their own North (13A, 14A) and South (13B, 14B) poles.

10 Door sensors 7 and 8 provide controller 6 with a "touch" signal which may be used to determine the presence of a user's hand in contact with the pads indicating that a user is about to open or close one of the doors (or has just opened or closed a door and is still in contact with it). As the touch sensitive pads 7 and 8 are provided on the compartment doors, the touch signals must somehow be transmitted to
15 controller 6 through the gap between door and cabinet. One way of achieving this is by providing wires through the hinge pins in the doors or by using the hinge pin as a conductor. This would ensure that the touch signal could be provided to controller 6 independent of whether the door is open or closed.

Alternatively, and more preferably, the touch signals are transmitted from the
20 door to the controller 6 without wires. This may be accomplished by providing an electrically conductive but non-magnetic cover over the permanent magnets in the compartment doors and wiring these to their respective touch sensitive pads. Further electrically conductive yet non-magnetic covers are also provided over the electromagnets in the refrigerator cabinet which are wired to the controller 6. In this
25 way, an electrical coupling is provided between the permanent magnet cover and the electromagnet cover such that an electrical touch signal may be passed through the air gap between the door and the cabinet 1. It will be appreciated that this signal transmission method will only work when the door is closed or nearly closed.

The following is an example of the preferred use of the present invention with
30 the refrigerator compartment. It will be appreciated that preferred operation of the invention in association with the freezer compartment or any other compartment is

the same.

In use and with reference to Figure 3, controller 6 first initialises then enters a standby mode at block 30 in which it checks whether the compartment door is open in decision block 31. This could be accomplished for example by providing a
5 mechanical sensor or switch would senses the position of door 4 and transmits an appropriate signal to controller 6. Alternatively a Hall Effect sensor could be provided to detect the presence of the door mounted permanent magnet 13 and transmit an appropriate signal to controller 6. In the preferred form of the present invention however, the door position is detected by sensing the inductive property of
10 electromagnet 11. It will be appreciated that reluctance to the flux produced by the electromagnet will be greater when the door is opened (a large air gap between the North and South poles) than when the door is closed and the flux is able to flow through the permanent magnet (with two very small air gaps). By sensing the reluctance of the magnetic circuit it is therefore possible to detect the open or closed
15 state of the door without the necessity of additional sensors.

If door 4 is found to already be open then a timer is started and a period T_4 is waited in block 38 before the door position is again detected in block 39. If the door is found to now still be open then a further delay of period T_4 is waited in block 38 before the door position is again detected. If it is found that the door has not been
20 closed for some length of time (for example 5 minutes) then it may be necessary to alert a user by, for example, energising a buzzer to produce an audible alarm.

If in block 39 the door is found to now be closed then at block 41 controller 6 energises electromagnet 11 to pull the door closed. This is accomplished by energising the electromagnet in a direction which will cause pole 11A to be a North
25 pole and pole 11B to be a South pole. Accordingly, the magnetic fields of the permanent magnet and the electromagnet will reinforce each other and the a closing force will be provided to door 4. The electromagnet is energised for a duration of T_5 seconds which has been calculated as sufficient to close the door. The electromagnet is then de-energised and the door will remain closed due to the attraction between
30 the permanent magnet in door 4 and the ferromagnetic core of electromagnet 11.

In block 40 controller 6 senses whether touch sensitive pad 7 has detected the

presence of a user's hand. In the preferred form of the present invention, a high frequency (for example a 150kHz "saw tooth" wave form) signal is provided to the touch sensitive pad 7 by an oscillator through a current limiting protection circuit and a capacitive filter (to block mains "hum" of 50 or 60 Hz). It is known that the human body appears as a capacitive load to ground of approximately 100pF. Accordingly, at 150 kHz the human body has an impedance of approximately 11k Ω . The touch switch 7 is provided with the high frequency wave form from a source impedance of, for example, 47k Ω so that human contact with the touch sensitive pad significantly attenuates the oscillator output. The oscillator output/touch switch voltage may then be filtered to remove the AC component of the touch signal which may then be provided to controller 6 as an average DC level. The average DC level could then be converted to a digital value by an Analogue to Digital Converter to simplify processing by a microprocessor.

If in block 40 it is decided that a user has not contacted the touch sensitive pad 7 then the standby mode is again entered at block 30 where controller 6 waits for touch pad 7 to be reactivated with all compartment doors closed.

If in block 40 it is found that a user has contacted the touch pad 7 then a user must be about to open door 4 and therefore control passes to block 33 where electromagnet 11 is energised in a direction such that pole 11A becomes a South pole and pole 11B becomes a North pole so that the magnetic fields of the permanent and electromagnets repel one another and the door is provided with an opening force for a duration of T_1 seconds. Duration T_1 is a sufficient time to allow door 6 to open a distance which will allow a user to easily be able to then pull the door fully open without having to pull against the attractive force between permanent magnet 13 and the core of electromagnet 11. If the door is found to then still be closed in block 34 then control returns to block 41 where the door is pulled closed again.

If the door is however open at decision block 34 then controller 6 initiates a timer for a duration of T_2 seconds at block 35 which is preferably a period of time sufficient to allow the average person to browse the contents of the refrigerator and withdraw or deposit items of food (for example, T_2 could range between 5 seconds and 30 seconds).

Once the timer has reached the predetermined duration T_2 , a check is made as to whether the door is still open at block 36. If the door is found to be closed (or nearly closed) then control passes to block 41 where the door is pulled closed and subsequent steps are carried out as has already been described. However, if the door is found to still be open then control passes to block 38 wherein a loop is entered at block 38 in which the state of the door is regularly (after a duration of every T_4 seconds). As mentioned above, if this loop is followed a predetermined number of times or if the door is found to be open for a predetermined duration of time then it may be necessary to raise an alarm to alert a user that the door requires closing.

Once the door is found to be nearly closed then control passes to block 41 where the door is pulled shut and subsequent steps carried out as already described.

It should be noted that the refrigerator door should, in use, ordinarily be biased in such a way to ensure that the door will tend to move in a direction which closes the door. This biasing could, for example, be achieved by ensuring that the front feet of the refrigerator are raised higher than the rear feet so that the front of the refrigerator cabinet is higher than the back. Alternatively, the hinge mechanism could be designed to provide a closing force to the door, for example by the use of springs or camming surfaces (causing the opening door to also be lifted against gravity) both of which require the user to add energy to the mechanism to open the door and which use this added energy to close the door once the user has released it.

If at block 31 the door is found to be closed prior to controller 6 sensing the user's touch at block 32 then the electromagnet 11 will be energised with current flowing in a direction which will produce a South pole at pole 11A and a North pole at pole 11B for a duration of T_1 seconds (for example a duration of between 0.5 and 2 seconds). As a result, the two South poles 11A and 13B and the two North poles 11B and 13A will each repel each other thereby allowing the user to easily open the door. If the repelling magnetic forces are large enough (and depending on the weight of the door and any items of food in the door) the door could be pushed open a slight amount by this repulsion.

Accordingly, it can be seen that at least in the preferred form of the present invention, a refrigerator door opening and closing system is provided which allows

the traditional door gasket to be redesigned to increase its insulating properties while also reducing the occurrence of compartment doors accidentally remaining slightly ajar after use. Accordingly, an increase in overall efficiency of a refrigerator incorporating the present invention is expected.

CLAIMS:

1. Door state changing apparatus for assisting a user to move a door between a closed state where the door is positioned adjacent a door frame and an open state comprising:
- 5 permanent magnet means on or attached to said door to provide a permanent magnetic field,
- electromagnet means on or attached to said door frame adjacent said permanent magnet means when said door is in said closed state, which
- 10 electromagnet means is energisable to provide a magnetic field in a first direction to reinforce said permanent magnetic field and energisable to provide a magnetic field in a second direction to oppose said permanent magnetic field
- door position detection means to detect the state of said door,
- user interface means to detect the presence of a user attempting to alter the
- 15 state of said door, and
- control means which receives input from said door position detection means and said user interface means and provides a control signal to energise said electromagnet means to provide a magnetic field in said first direction if said user interface means indicates a user is attempting to alter the state of said door and said
- 20 door position detection means indicates that said door is in said open state and provides a control signal to energise said electromagnet means to provide a magnetic field in said second direction if said user interface means indicates a user is attempting to alter the state of said and said door position detection means indicates that said door is in said closed state.
- 25 2. Door state changing apparatus as claimed in claim 1 wherein said electromagnet means is de-energised when said door position detection means indicates that said door is in said closed position.
3. Door state changing apparatus as claimed in either claim 1 or claim 2 wherein said control means includes delay means which provide a time delay between said
- 30 door position detection means detecting said closed state and de-energising said electromagnet means.

4. Door state changing apparatus as claimed in any one of claims 1 to 3 wherein said user interface means include sensing means which cover a region of the surface of said door.

5. Door state changing apparatus as claimed in any one of claims 1 to 4 wherein said user interface means comprise door state change direction detecting means which provide said control means with an indication of the direction of the change of state of said door and to cause said control means to energise said electromagnet means to provide a magnetic field in said first direction if said door state change direction detecting means indicates a user is attempting to alter the state of said door from an open state to a closed state and to cause said control means to energise said electromagnet means to provide a magnetic field in said second direction if said door state change direction detecting means indicates a user is attempting to alter the state of said door from a closed position to an open position.

6. Door state changing apparatus as claimed in any one of claims 1 to 5 wherein the strength of the magnetic field provided by said electromagnet is variable.

7. Door state changing apparatus as claimed in claim 6 wherein the strength of said magnetic field in said second direction is greater than or equal to the strength of said permanent magnetic field.

8. Door state changing apparatus as claimed in any one of claims 1 to 7 wherein said door position detection means comprise proximity detection means provided on or attached to said door frame which detects the proximity of said permanent magnet means.

9. Door state changing apparatus as claimed in claim 8 wherein said proximity detection means comprise means to sense the inductance of said electromagnet means.

10. Door state changing apparatus as claimed in any one of claims 1 to 9 wherein said permanent magnet means is formed in a substantially "U" shape with the ends of the legs of said "U" directed towards said electromagnet means and with opposing magnetic poles at the end of each leg.

11. Door state changing apparatus as claimed in any one of claims 1 to 10 wherein said electromagnet means comprise a substantially "U" shaped core of

magnetically permeable material and an energisable winding around said core, the ends of the legs of said "U" shape being directed towards the legs of said permanent magnet means.

12. Door state changing apparatus as claimed in any one of claims 1 to 11

5 wherein said permanent magnet means is positioned on or near the centre line of said door.

13. A home appliance including a cabinet and a door hingeably connected to said cabinet and closeable against a door frame said appliance including door state changing apparatus for assisting a user to move said door between a closed state and
10 an open state where said door is positioned adjacent said door frame and an open state, said door state changing apparatus comprising:

permanent magnet means on or attached to said door to provide a permanent magnetic field,

electromagnet means on or attached to said door frame adjacent said
15 permanent magnet means when said door is in said closed state, which electromagnet means is energisable to provide a magnetic field in a first direction to reinforce said permanent magnetic field and energisable to provide a magnetic field in a second direction to oppose said permanent magnetic field

20 door position detection means are also provided to detect the state of said door,

user interface means to detect the presence of a user attempting to alter the state of said door, and

control means which receives input from said door position detection means
25 and said user interface means and provides a control signal to energise said electromagnet means to provide a magnetic field in said first direction if said user interface means indicates a user is attempting to alter the state of said door and said door position detection means indicates that said door is in said open state and provides a control signal to energise said electromagnet means to provide a magnetic
30 field in said second direction if said user interface means indicates a user is attempting to alter the state of said and said door position detection means indicates

that said door is in said closed state.

14. A refrigerator including door state changing apparatus as claimed in any one of claims 1 to 12.

5 15. A refrigerator including door state changing apparatus substantially as herein described with reference to and as illustrated by the accompanying drawings.



FIG. 1

FIG. 2



INTERNATIONAL SEARCH REPORT

International application No.

PCT/NZ 99/00139

A. CLASSIFICATION OF SUBJECT MATTER		
Int Cl ⁶ : E05F 1/00		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
IPC E05F 1/00		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
WPAT: E05F or F25D 23/02 and (open: or ajar) and (clos: or shut:) and magnet: and electromagnet:		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 293 020 A (HAN) 8 March 1994 whole document	1-15
A	Patent Abstracts of Japan, JP 7-018943 A (ENGETSU) 20 January 1995 Abstract	1-15
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex		
<p>* Special categories of cited documents:</p> <p>"A" Document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>		
Date of the actual completion of the international search 19 October 1999		Date of mailing of the international search report 27 OCT 1999
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200 WODEN ACT 2606 AUSTRALIA E-mail address: pct@ipaaustralia.gov.au Facsimile No.: (02) 6285 3929		Authorized officer PETER WARD Telephone No.: (02) 6283 2129

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NZ 99/00139

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 3 837 547 A (MAIER) 10 May 1990 Abstract	1-13
A	Derwent Abstract Accession No 93-091578/11, Class Q47, SE 9200194 A (ELECTROLUX AB) 30 November 1992 Abstract	1-13

Information on patent family members

International application No.
PCT/NZ 99/00139

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report		Patent Family Member	
US	5 293 020	EP	550 897
		JP	05-2486 41

END OF ANNEX

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.